



Branch Reduced 45° Branch with spigots suitable for EF Coupler Welding									
All spigots can be extended/pupped to any length									
Dia	SDR 11	Branch	≥Z	≥L	Dia	SDR17	Branch	≥Z	≥L
125	12.8Bar	110	238	471	125	8Bar	110	238	471
140	12.8Bar	110	354	556	140	8Bar	110	354	556
160	12.8Bar	110-125	368	556	160	8Bar	110 & 125	368	556
180	12.8Bar	110-140	382	556	180	8Bar	110-140	382	556
200	12.8Bar	110-160	446	656	200	8Bar	110-160	446	656
225	12.8Bar	110-180	464	656	225	8Bar	110-180	464	656
250	12.8Bar	110-200	532	756	250	8Bar	110-200	532	756
280	12.8Bar	110-225	553	756	280	8Bar	110-225	553	756
315	12.8Bar	110-250	628	856	315	8Bar	110-250	628	856
355	12.8Bar	110-280	656	856	355	8Bar	110-280	656	856
400	12.8Bar	110-315	688	856	355	8Bar	110-315	688	856
450	12.8Bar	110-315	723	856	400	8Bar	110-315	723	856
500	12.8Bar	125-400	743	920	450	8Bar	125-400	743	920
560	12.8Bar	160-450	773	1040	500	8Bar	160-450	773	1040
630	12.8Bar	225-560	828	1000	560	8Bar	225-560	828	1000

We reserve the right to change Z, L & I measures at any time