



With exposed heating coils for optimal heat transfer, large insertion depth, wide fusion zones plus cold zones at the end and in the middle to prevent the flow of molten material, for use without holding devices. With separate fusion zones.

UB d 1000 and above can only be fused with the FRIAMAT XL.

From d 560 with pre-heating technology.  
Special sizes, pressure stages and designs on request.



## PE 100 SDR 17

Maximum working pressure 10 bar (water)/5 bar (gas)

d	Order Ref.	Stock-status	BX	PU	D	L	Weight kg/each
315	<b>616529</b>	1	1	18	356	280	5.880
355	<b>616530</b>	1	1	9	400	290	7.600
400	<b>616531</b> ①	1	1	9	450	300	10.100
450	<b>616532</b> ①	1	1	4	506	320	13.650
500	<b>616533</b> ①	1	1	2	562	350	18.250
560	<b>615706</b> ①	1	1	2	630	380	24.190
630	<b>615726</b> ①	1	1	2	710	420	34.870
710	<b>615994</b> ①	1	1	2	800	442	46.000
800	<b>616290</b> ①	1	1	1	900	500	65.900
900	<b>616345</b> ①	1	1	1	1024	500	91.500
1000	<b>616403</b> ①	1	1	1	1130	610	128.000
1200	<b>616416</b> ①	3	1	1	1356	670	205.000

① separate fusion zones