



25.80.01.103 PE100 V-Bund lang gerillt **SDR11** schwarz
PE100 Flange adaptor spigot long grooved **SDR11** black

Teil / Item	D [mm]	e [mm]	D2 [mm]	D3 [mm]	H [mm]	L [mm]	z [mm]	KG	VE1	VE2
2333 07F0 15	25	2,3	58	33	9,0	51	90	0,040	10	180
2333 08F0 15	32	3,0	68	40	10,0	57	95	0,060	10	80
2333 09F0 15	40	3,7	78	50	11,0	55	100	0,080	10	60
2333 10F0 15	50	4,6	88	61	12,0	63	115	0,13	10	60
2333 11F0 15	63	5,8	102	75	14,0	78	122	0,21	5	40
2333 12F0 15	75	6,8	122	89	16,0	84	130	0,32	1	18
2333 13F0 15	90	8,2	138	105	17,0	98	145	0,48	1	12
2333 14F0 15	110	10,0	158	125	18,0	102	155	0,71	1	12
2333 15F0 15	125	11,4	158	132	26,0	115	170	0,93	1	8
2333 16F0 15	140	12,7	188	155	25,0	112	175	1,26	1	4
2333 17F0 15	160	14,6	212	175	25,0	122	185	1,66	1	6
2333 18F0 15	180	16,4	212	180	30,0	160	195	1,94	1	4
2333 19F0 15	200	18,2	268	232	32,0	123	205	3,14	1	-
2333 20F0 15	225	20,5	268	235	32,0	143	215	3,40	1	-
2333 21F0 15	250	22,7	320	285	35,0	150	235	5,25	1	-
2333 22F0 15	280	25,4	320	291	35,0	178	253	5,82	1	-
2333 23F0 15	315	28,6	370	335	35,0	172	257	8,05	1	-
2333 24F0 15	355	32,2	430	373	40,0	195	285	11,3	1	-
2333 25F0 15	400	36,3	475	427	46,0	215	315	16,1	1	-
2333 26F0 15	450	40,9	575	514	60,0	196	326-340	26,0	1	-
2333 27F0 15	500	45,4	575	530	60,0	200	330-360	29,0	1	-
2333 28F0 35	560	50,8	685	615	60,0	240	370-380	47,1	1	-
2333 29F0 15	630	57,2	685	642	65,0	250	360-375	42,3	1	-

25.80.01.063 PE100 V-Bund lang gerillt **SDR17** schwarz
PE100 Flange adaptor spigot long grooved **SDR17** black

Teil / Item	D [mm]	e [mm]	D2 [mm]	D3 [mm]	H [mm]	L [mm]	z [mm]	KG	VE1	VE2
2334 11F0 15	63	3,8	102	75	14	78	122	0,18	5	40
2334 12F0 15	75	4,5	122	89	16	84	130	0,27	1	18
2334 13F0 15	90	5,4	138	105	17	98	145	0,38	1	12
2334 14F0 15	110	6,6	158	125	18	102	155	0,56	1	12
2334 15F0 15	125	7,4	158	132	18	122	170	0,63	1	8
2334 16F0 15	140	8,3	188	155	18	119	175	0,90	1	4
2334 17F0 15	160	9,5	212	175	18	129	185	1,12	1	6
2334 18F0 15	180	10,7	212	180	20	175	195	1,36	1	4
2334 19F0 15	200	11,9	268	232	24	131	205	2,28	1	-
2334 20F0 15	225	13,4	268	235	24	151	215	2,33	1	-
2334 21F0 15	250	14,8	320	285	25	160	235	3,60	1	-
2334 22F0 15	280	16,6	320	291	25	188	253	4,16	1	-
2334 23F0 15	315	18,7	370	335	25	182	257	5,56	1	-
2334 24F0 15	355	21,1	430	373	30	195	275	7,83	1	-
2334 25F0 15	400	23,7	482	427	33	227	315	11,1	1	-
2334 26F0 15	450	26,7	575	514	46	196	326-340	18,3	1	-
2334 27F0 15	500	29,7	575	530	46	224	330-360	20,0	1	-
2334 28F0 35	560	33,2	685	615	50	250	370-380	27,2	1	-
2334 29F0 15	630	37,4	685	642	50	260	410	29,3	1	-